

Specification of Toshiba e-Studio 3028A Copier Machine With RADF



General Feature		
Copy / Print Speed (ppm)		30
Warm-up Time	After power-on	Approx. 20 sec. (68F/ 20C)
	From sleep mode	Less than 14 sec. (68F/ 20C)
	From low power mode	Less than 14 sec. (68F/ 20C)
Memory		Std. 4GB (Main memory + Page memory)
Storage		Std. 128 GB (SSD) (Shared for all imaging functions)/ Opt. 512 GB (SSD) or 320 GB (HDD)
Dimension (W × D × H)		585 × 586 × 787mm / 23" × 23.1" × 31"
Weight		Approx. 54.5 kg / 120.0 lbs (Incl. Drum / Developer)
Input Paper Capacity		1,200 sheets (550x2+100)
Available Paper Weight		Cassettes: A5R-A3, 60-256 g/m² Bypass Single Feed: 100x148 mm-A3, 52-256 g/m², Multi-Feed: 100x148 mm-A3, 60-256g/m² Banner paper (up to 305 x 1,200 mm, 90-163g/m²)
Available Paper size		Single-Feed : 100 x 148 mm to A3 / 100 x 148 mm to LD
Document feeder		Optional 300-sheet DSDf or 100-sheet RADF
Duplexing		Standard
Finishing Option		Multi-Position stapling finisher, Saddle Stitching Finisher, Inner Finisher, Job Separator
Copier Feature		
First Copy Time		Less than 4.3 sec.
Resolution	600 dpi x 600 dpi, 1bit *1	
	2,400 dpi (Equivalence) x 600 dpi (with smoothing) *2	
	*1 or *2 is selected by copy mode automatically. No selectable by user.	
Gradation		256 steps
Multiple Copy		Up to 999 Copies/ Ten key input
Printer Feature		
Resolution		All PDL: 600 dpi x 600 dpi, 1bit / 2400 dpi (Equivalence) x 600 dpi (with smoothing) PS only: 1,200 dpi x 1,200 dpi, 2bit (3,600 dpi (Equivalence) x 1,200 dpi)
PDL		PCL5e/c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Interface	Standard	10/100/1000baseT, USB 2.0 High Speed USB
	Option	IEEE802.11b/g/n, Bluetooth
Scanner Feature		
Resolution		100/150/200/300/400/600dpi
Scan Speed	RADF	73 ppm (100,150,200,300 dpi), 62 ppm (400 dpi), 50 ppm (600 dpi)
Data format	Standard	JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF-Multi/Single Page, XPS-Multi/Single Page
(Color)	Option	DOCX-Multi/Single Page, XLSX-Multi/Single Page, PPTX-Multi/Single Page
Scan features		Scan to File, Scan to E-mail, Scan to e-Filing, Scan to WS Scan, Scan to USB, Scan Preview
Fax Feature (option)		
Communication mode / Modem Speed		Super G3, G3 / 33.6 kbps- 2.4 kbps (automatic fallback)
Data Compression		JBIG, MMR, MR, MH
Number of Lines (Std. / Max.)		2-Jan
Phonebook		3,000 stations
Security Feature		
Standard		TPM 2.0, Anti-malware, Secure Boot, Self-Encrypting SSD, Private Print, Encrypted/digitally Signed PDF, User Authentication, Role Based Access Control, IP/MAC address filtering, TLS, Data Overwrite, 802.1X, SMBv3, Password policy, SNMPv3, Confidentiality setting, Tampering Prevention of Firmware, Hardcopy Security Printing, SCEP